PCT

9300443





INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5: (11) International Publication Number: WO 94/19931 A01K 1/12, A01J 7/00 A1 (43) International Publication Date: 15 September 1994 (15.09.94)

(21) International Application Number: PCT/NL94/00060 DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). (22) International Filing Date: 10 March 1994 (10.03.94)

NL

Published (30) Priority Data:

11 March 1993 (11.03.93)

(71) Applicant (for all designated States except US): PROLION B.V. [NL/NL]; Kromme Spieringweg 289B, NL-2141 BS Vijfhuizen (NL).

(72) Inventor: and (75) Inventor/Applicant (for US only): OOSTERLING, Pieter, Adriaan [NL/NL]; Sikkelstraat 53, NL-2151 CP Nieuw-Vennep (NL).

(74) Agent: HOORWEG, Petrus, Nicolaas; Arnold & Siedsma, Sweelinckplein 1, NL-2517 GK The Hague (NL).


(81) Designated States: CA, JP, US, European patent (AT, BE, CH,

With international search report. In English translation (filed in Dutch).

(54) Title: A METHOD AND A DEVICE FOR SURVEYING ANIMAL FUNCTIONS

(57) Abstract

Method and device for surveying animal functions by means of an animal manipulating apparatus such as a milking device, in particular a milking robot, provided with animal guiding members, animal contacting means and/or animal nursing means, wherein a programmable control system is used to control said means in order to subject the animal to a predetermined sequence of operations, that is for instance, positioning, applying of teat cups, milking and subsequent or simultaneous feeding, checking the specific animal behaviour and removing the animal, wherein the operations to which the animal is subjected are programmed in respect of time and that at least one warning signal is generated by the control system if a time determined in the program for an operation is exceeded or not attained, in order to detect non-function or aberrant functions of the animal.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	TE.	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Кепуа	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
CG	Congo		of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SI	Slovenia
cī	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovakia
CM	Cameroon	LI	Liechtenstein	SN	Senegal
CN	China	LK	Sri Lanka	TD	Chad
cs	Czechoslovakia	LU	Luxembourg	TG	Togo
cz	Czech Republic	LV	Latvia	TJ	Tajikistan
DE	Germany	MC	Monaco	TT	Trinidad and Tobago
DK	Denmark	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	US	United States of America
FI	Finland	ML	Mali	UZ	Uzbekistan
FR	France	MN	Mongolia	VN	Vict Nam
GA	Gebon				

1

A METHOD AND A DEVICE FOR SURVEYING ANIMAL FUNCTIONS

The invention relates to a method for surveying animal functions by means of an animal manipulating apparatus such as a milking device, in particular a milking robot, provided with animal guiding members, 5 animal contacting means and/or animal nursing means, wherein a programmable control system is used to control said means in order to subject the animal to a predetermined sequence of operations, that is for instance, positioning, applying of teat cups, milking and subsequent or simultaneous feeding, checking the specific animal behaviour and removing the animal.

It has become increasingly usual in the cattle farming industry to use program-controlled machines to manipulate animals. Particular reference can be made here 15 to a milking robot, wherein the animal is guided wholly unattended via fence-like guide means to a manipulation location, making use of the Pavlovian behaviour of the animal, namely that a reward is provided in the form of feed. The animals herein display a type of behaviour 20 which proceeds according to the same pattern during each operation, so that the device can be pre-programmed on the basis thereof. Such devices further have the possibility of checking particular occurring functions of the animal, whereby for instance a picture of the health of 25 the animal can be established. It is for instance usual in the case of cows to detect draughtiness and diseases by means of a temperature sensor in milking systems.

The invention has for its object however to extend surveying to all animal functions, whereby it becomes

30 possible using the programmed device to establish abnormal functions of the animal and to respond thereto. These malfunctions or abnormal functions can for instance be non-appearance at the programmed device as a result of external causes, for example breaking a leg. Other possibilities are the animal becoming entangled in the device,

wherein the device can function per se normally.

The invention has for its object to provide a device wherein the above stated surveying can be performed in simple manner. The device according to the invention is 5 distinguished in that the operations to which the animal is subjected are programmed in respect of time and that at least one warning signal is generated by the control system if a time determined in the program for an operation is exceeded or not attained, in order to detect nonfunction or aberrant functions of the animal.

The invention is based on the idea that each operation on the animal requires a predetermined time, which time can per se differ per type of or per individual animal. Should the predetermined time be exceeded in the sequence of operations the device, which can function per se well, then detects that there is something wrong with the function of the animal. Non-attainment of the predetermined time can also be an indication that something is wrong. This can happen when the milk production of the animal is too small, wherein the effective milking time is shorter than normal. Since such programmed devices are usually embodied with animal recognition means the supervisor, who does not have to be permanently present at the device, can be warned, whereafter he can take action.

25 A further improvement is obtained by a multiple signalling system for the supervisor, such as for instance a semaphone or a telephone paging device, wherein the supervisor is informed of the urgency of the call. Thus in the case of non-appearance of the animal the supervisor can still delay, while in the case of a break or the like he can take immediate action.

The invention is further elucidated in the figure description hereinbelow of an embodiment.

An embodiment of a device according to the invention 35 is shown in the accompanying drawing of a milking system for cows.

The figure shows schematically the control of the system. Therein 6 is the central control system which is

3

operated by means of terminal 9. The control system gives actuating signals to the different components of the device.

These components can consist among others of the

5 mechanically movable guide means, such as fences 11, the
identification system 12, the feeding system 13, the
placing system 14 and the milking system 15. Arranged in
these systems are sensors which check the operation of
each system, in particular whether the control signals

10 have the desired result. Associated with each of these
systems is a control system 1 to 5, wherein in the feedback system 1a to 5a the signal processing of the operation of the sensors checking and controlling the system
takes place. It is possible for the control system of a

15 component of the device to be built up of multiple control groups, such as indicated at 4 and 4'.

The behaviour of the cow is detected with the sensors 10, the data from which is processed as sensor information in the control systems of the diverse components. This sensor information is moreover passed on to the central control system 6.

In the central control system the different sensor data is combined, whereby on the one hand the operation of the device is optimalized and on the other hand the functions and state of health of the cow are detected, checked and analyzed. A comparison is made as to whether the functions correspond with the preprogrammed pattern of the relevant animal and with that which can be expected in the occurring situation. Should non-function or erroneous function be detected, the control system then establishes that the supervisor must be warned, wherein a choice is also made from a number of possible types of message. Using the paging system 8, for instance a semaphone installation, the supervisor is warned and informed of the steps taken and the urgency of the message.

The steps can differ herein in accordance with the time at which the detection is made: aberrations for which the cow is kept in the milking parlour during the

day and the supervisor is paged will only result during the night in the animal being separated. Paging of the supervisor can also be accompanied by an indication of the urgency thereof: in situations where the cow is standing quietly in the milking parlour there is little urgency, while for instance the passageway being blocked for 15 minutes without there being an apparent reason therefor is an urgent situation.

Examples of situations wherein warning signals are generated by the control system and the possible responses thereto are given below, wherein this enumeration is not limiting for the options to be included in the programming.

The amount of milk a cow gives per cycle can be

15 converted to a time indication. If the difference is for
instance 25% less than the expected amount the supervisor
is warned. If all teats are connected to the milking
system and no milk comes from one of the quarters, also
after repeated connecting, this likewise gives cause to
20 warn the supervisor.

Signalling is also possible as to whether the cow has arrived at the milking parlour. If for instance the second milking period in a day is between 8.00 hours and 11.00 hours in the morning and at 10.00 a number of cows 25 have not yet appeared, the supervisor then receives a signal that one or more cows have yet to appear. This can for instance be printed out on a printer. Five to ten minutes before the period has elapsed the supervisor is warned if there are then still animals which have not yet 30 been milked. He can then investigate the reasons why the relevant animals have not gone to the milking parlour.

If an animal is detected, and optionally identified, in the passageway to the milking parlour, and has not arrived in the milking parlour after for instance 15 minutes, then there is a problem with the animal. The supervisor is warned; the relevant section is closed off; milking is stopped and the system cleaned and the fences opened.

It may also occur that an animal is particularly restless, for instance because it is in pain. The system detects this by the high frequency of the movements, for instance during arranging of the milking cluster and/or the movements of a leg. If this restlessness is not extreme the cow can be led into a separation stall. If on the other hand the restlessness is considerable, the cow can then remain standing and the supervisor is warned.

Other situations in which the control system signals 10 that something is wrong with a cow are:

The cow becomes unwell and lies in the parlour or at the entrance or exit.

The cow stands the wrong way round in the parlour.

The cow is jammed with head or body between fence, 15 feeding fence and the like.

The cow has slipped and broken a leg.

the cow has pushed over one of the fences and is lying among the debris.

Below are situations which can be detected in terms 20 of time:

The fence is open, the presence of the cow is signalled but identification at the feeding fence is not forthcoming.

The cow does not leave the milking parlour.

25 The cow does not eat from the feed trough.

There are no teats or no udder to detect.

The fences do not close or will not open, caused by the presence of the cow.


The moving mechanism of the milking device is 30 blocked.

The above situations result in signals to the supervisor which may or may not differ. Essential however is that the above stated aberrations are not related to the operation of the programmed device itself but to the 35 manner in which the animal functions in such a device.

The invention is not limited to the above described embodiment.

CLAIMS

- 1. Method for surveying animal functions by means of an animal manipulating appliance such as a milking apparatus, in particular a milking robot, provided with animal quiding members, animal contacting means and/or 5 animal nursing means, wherein a programmable control system is used to control said means in order to subject the animal to a predetermined sequence of operations, that is, for instance positioning, applying of teat cups, milking and subsequent or simultaneous feeding, checking 10 the specific animal behaviour and removing the animal, characterized in that the operations to which the animal is subjected are programmed in respect of time and that at least one warning signal is generated by the control system if a time determined in the program for an opera-15 tion is exceeded or not attained, in order to detect nonfunction or aberrant functions of the animal.
 - 2. Method as claimed in claim 1, characterized in that the signal is transmitted in wireless manner to a remotely located receiver.
- 3. Method as claimed in claim 1 or 2, characterized in that signals of differing strength and/or type are generated depending on exceeding of the time in a determined program location.
- 4. Program-controlled animal manipulating device
 25 such as a milking robot for performing the method as
 claimed in claims 1-3, characterized in that the program
 control is performed with a signal-generating circuit
 which responds as soon as a pre-programmed time duration
 in the control has been exceeded.



A. CLASSIFICATION OF SUBJECT MATTER IPC 5 A01K1/12 A01J7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

 $\begin{array}{ll} \mbox{Minimum documentation searched (classification system followed by classification symbols)} \\ \mbox{IPC 5} & \mbox{A01K} & \mbox{A01J}. \end{array}$

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUM	MENTS CONSIDERED TO BE RELEVANT	
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,O 091 892 (ALFA-LAVAL) 19 October 1983 see page 1, line 30 - page 3, line 12	1
	see page 9, line 34 - page 11, line 11 see claims 1-6; figures 1-3	•
A	EP,A,O 320 496 (VAN DER LELY) 14 June 1989 see column 1, line 9 - line 51 see column 4, line 17 - line 58 see claims 1,10; figures	1
A	EP,A,O 188 303 (VAN DER LELY) 23 July 1986 see page 1, line 13 - page 3, line 2 see page 7, line 25 - page 8, line 9 see page 9, line 29 - page 10, line 22; figures	1
	-/	

Date of the actual completion of the international search 14 June 1994 Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2	*& document member of the same patent family Date of mailing of the international search report 27. 06. 94 Authorized officer
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but	cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
"E" earlier document but published on or after the international filing date	"X" document of particular relevance; the claimed invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the

1

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.



		PCT7NL 94/00060	
	ation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages		Relevant to claim No.
A	EP,A,O 189 954 (VAN DER LELY) 6 August 1986 see page 1, line 18 - line 26 see page 5, line 23 - line 33 see page 9, line 1 - line 13 see page 15, line 17 - line 26 see page 19, line 23 - page 20, line 35; figures 1,2		1

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

1

INTERNATIONAL SEARCH REPORT

n patent family members

Inter Application No
PCT No. 94/00060

Patent document cited in search report	Publication date	Patent fa membe		Publication date
EP-A-0091892	19-10-83	SE-B- DE-A- SE-A- US-A-	430559 3378349 8202278 4508058	28-11-83 08-12-88 09-10-83 02-04-85
EP-A-0320496	14-06-89	NL-A- DE-A- DE-A- DE-T- EP-A,B EP-A,B	8500088 3681924 3687273 3687989 3687989 0188303 0319523	18-08-86 21-11-91 21-01-93 15-04-93 30-09-93 23-07-86 07-06-89
EP-A-0188303	23-07-86	NL-A- DE-A- DE-A- DE-A- DE-T- EP-A- EP-A,B	8500088 3681924 3687273 3687989 3687989 0320496 0319523	18-08-86 21-11-91 21-01-93 15-04-93 30-09-93 14-06-89 07-06-89
EP-A-0189954	06-08-86	NL-A- NL-A- NL-A- DE-A- DE-D- EP-A- EP-A- EP-A- EP-A-	8500089 8500090 8500091 3684619 3689481 0332229 0332230 0332231	18-08-86 18-08-86 18-08-86 07-05-92 10-02-94 13-09-89 13-09-89 13-09-89